



形状・材質一覧

発泡目地棒

- 材質はポリスチレンで製品色は茶色です。
- 釘穴はなく用途に応じて何処にでも釘打ちが出来、鋸切断可能、吸率極小。(基本釘打間隔は15～30cmを目安)
- メタルフォームに接着の場合はボンドG200、K-10をご使用ください。
- 定着は2mですが別注サイズ長尺物製作賜ります。

※一部受注生産品もございます。



品番	A(mm)	B(mm)	C(mm)
M-17S	6	6	4
M-17W	6	6	4
M-15S	9	6	7
M-15W	9	6	7
M-14S	9	9	6.5
M-14W	9	9	6.5
M-3S	10	10	7
M-3W	10	10	7
M-6S	12	9	9
M-6W	12	9	9
M-13S	12	12	9
M-13W	12	12	9
M-12S	12	15	8
M-12W	12	15	8
M-5S	15	9	12
M-5W	15	9	12
M-2S	15	10	10
M-2W	15	10	10
M-16S	15	10	12
M-16W	15	10	12
M-11	15	12	8
M-4S	15	12	12
M-4W	15	12	12
M-1S	15	15	10

品番	A(mm)	B(mm)	C(mm)
K-24W	30	12	25
K-4S	30	15	20
K-4W	30	15	20
K-14S	30	15	25
K-14W	30	15	25
KG-2	30	15	
KG-4	30	20	
K-13S	30	20	20
K-13W	30	20	20
K-12S	30	20	25
K-12W	30	20	25
K-23W	30	25	15
K-22S	30	25	20
K-22W	30	25	20
K-1S	30	25	25
K-1W	30	25	25
K-21S	30	30	20
K-21W	30	30	20
K-27S	30	30	25
K-27W	30	30	23
K-34S	30	50	20
K-35W	30	50	12
K-51S	35	15	25
K-7S	35	20	25

M-1W	15	15	10
M-22S	15	15	12
M-22W	15	15	12
M-18S	15	20	10
M-18W	15	20	10
KG-1	20	10	
M-7	20	10	10
M-19W	20	10	10
K-6S	20	10	15
K-6W	20	10	15
K-26S	20	10	18
K-25S	20	12	14
K-25W	20	12	14
TM-23S	20	20	10
TM-23W	20	20	10
KG-3	20	15	
K-3S	20	15	15
K-3W	20	15	15
M-LS	20	20	15
M-LW	20	20	15
M-21S	20	25	10
M-21W	20	25	10
K-9S	25	10	20
K-9W	25	10	20
K-8S	25	15	15
K-8W	25	15	15
K-5S	25	15	20
K-5W	25	15	20
K-2S	25	20	20
K-2W	25	20	20
M-20S	25	25	5
M-20W	25	25	5
K-10S	25	25	10
K-10W	25	25	10
K-17S	25	25	20
K-17W	25	25	20
K-16S	25	30	19
K-16W	25	30	19
K-24S	30	12	25

K-7W	35	20	25
KG-5	40	20	
K-18S	40	20	35
K-18W	40	20	35
K-11S	40	25	25
K-11W	40	25	25
K-15S	40	25	30
K-15W	40	25	30
K-20S	40	30	30
K-20W	40	30	30
K-37S	50	20	40
K-37W	50	20	40
K-42S	50	20	45
K-42W	50	20	45
K-43S	50	25	45
K-43W	50	25	45
K-36S	50	30	30
K-36W	50	30	30
K-19S	50	30	40
K-19W	50	30	40
K-44S	50	40	40
K-44W	50	40	40
K-33W	50	50	30
K-32S	50	50	40
K-29W	60	30	50
K-28S	60	30	55
K-31W	70	30	60
K-30S	70	30	65
K-38W	80	30	70
K-39S	80	30	75
K-45S	85	40	80
K-47S	85	45	80
K-40W	100	30	90
K-41S	100	30	95
K-46S	100	40	95
K-48S	100	45	95